

Roles of Scrambling and Noise in Information Processing with Quantum Systems


Thiparat Chotibut (Thip)

Chula Intelligent and Complex Systems Research Unit,
Department of Physics,
Chulalongkorn University, Bangkok, Thailand

October 8, 2025

100 Years of Quantum Physics
Recontres du Vietnam
ICISE, Quy Nhon

Input



Output




Roles of Scrambling and Noise in Information Processing with Quantum Systems

Thiparat Chotibut (Thip)


Chula Intelligent and Complex Systems Research Unit,
Department of Physics,
Chulalongkorn University, Bangkok, Thailand

October 8, 2025


100 Years of Quantum Physics
Recontres du Vietnam
ICISE, Quy Nhon




Statistical mechanics/dynamics of learning algorithms on quantum substrate



Quantum Extreme Learning Machine (QELM)




Quantum Reservoir Computing (QRC)



Acknowledgement

Mehrad Sahebi Giorgio Facelli Weijie Xiong (EPFL)



Owen Agnel (Oxford)



Supanut Thanasilp
(Chulalongkorn)




Zoe Holmes
(EPFL)

Why QELM and QRC? A Brief Detour: The Quest for Quantum Advantages

Ideal (**Fault-tolerant**) quantum computational advantages

Textbook algorithms: Shor's, Grover's, HHL, etc.






Why QELM and QRC? A Brief Detour: The Quest for Quantum Advantages

✗ Ideal (**Fault-tolerant**) quantum computational advantages

Textbook algorithms: Shor's, Grover's, HHL, etc.

✓ Noisy Intermediate-Scale Quantum (NISQ) Era

Variational Quantum Algorithms (VQAs)




Why QELM and QRC? A Brief Detour: The Quest for Quantum Advantages

✗ Ideal (**Fault-tolerant**) quantum computational advantages



Textbook algorithms: Shor's, Grover's, HHL, etc.

✓ Noisy Intermediate-Scale Quantum (NISQ) Era

Variational Quantum Algorithms (VQAs)



✗ **Curse of Dimensionality**
Untrainability (Barren Plateaus)



Why QELM and QRC? A Brief Detour: The Quest for Quantum Advantages

✗ Ideal (**Fault-tolerant**) quantum computational advantages

Textbook algorithms: Shor's, Grover's, HHL, etc.

✓ Noisy Intermediate-Scale Quantum (NISQ) Era

Variational Quantum Algorithms (VQAs)



✗ **Barren plateaus** are ubiquitous

No variational parameters. Use NISQ devices to generate
high dimensional feature maps for **Quantum Machine Learning**

Quantum Kernel Methods

? Quantum Extreme Learning Machines (QELMs)

? Quantum Reservoir Computing (QRC)





quantum scrambling to the rescue?

Examples of Non-Variational Algorithm: Reservoir Computing

Edge-of-chaos recurrent network reservoir

kuramoto-sivashinsky spatiotemporal chaos





J. Pathak et. al. *Phys. Rev. Lett.* 120, 024102, 2018

Examples of Non-Variational Algorithm: Reservoir Computing


Edge-of-chaos recurrent network reservoir

kuramoto-sivashinsky spatiotemporal chaos





J. Pathak et. al. *Phys. Rev. Lett.* 120, 024102, 2018

Quantum scrambling reservoir (Chaotic Ising)




(a) Lorenz attractor




Seems promising for 10+ qubits, but will this scale?

K. Fujii, K. Nakajima, *Reservoir Computing* 423-450, 2021

Quantum Reservoir Computing in a Nutshell



Quantum Reservoir Computing in a Nutshell




SYNOPSIS

Quantum Machine Learning Goes Photonic

April 16, 2024 • *Physics* 17, s41

Measuring a photon’s angular momentum after it passes through optical devices teaches an algorithm to reconstruct the properties of the photon’s initial quantum state.



A. Suprano et al. [1]

FEATURED IN PHYSICS | EDITORS' SUGGESTION

Experimental Property Reconstruction in a Photonic Quantum Extreme Learning Machine

[Alessia Suprano](#) ^{1,*}, [Danilo Zia](#) ^{1,*}, [Luca Innocenti](#) ^{2,*}, [Salvatore Lorenzo](#) ^{2,*}, [Valeria Cimini](#) ¹, [Taira Giordani](#) ¹, [Ivan Palmisano](#) ³, [Emanuele Polino](#) ^{1,4}, [Nicolò Spagnolo](#) ¹ et al.

Phys. Rev. Lett. **132**, 160802 – Published 16 April, 2024
DOI: <https://doi.org/10.1103/PhysRevLett.132.160802>

nature communications

Article

<https://doi.org/10.1038/s41467-024-51161-8>


Microwave signal processing using an analog quantum reservoir computer

Received: 12 February 2024 | Accepted: 31 July 2024 | Published online: 30 August 2024


Alen Senanian ^{1,2}, Sridhar Prabhu ^{1,2}, Vladimir Kremenetski ², Saswata Roy ^{1,2}, Yingkang Cao ^{3,4}, Jeremy Kline ^{2,7}, Tatsuhiro Onodera ^{2,5}, Logan G. Wright ^{2,5,8}, Xiaodi Wu ^{3,4}, Valla Fatemi ² & Peter L. McMahon ^{2,6}

Seems promising for small quantum reservoirs, but will this scale?


Quantum Reservoir Computing in a Nutshell



Mathematical framework



Quantum Reservoir Computing in a Nutshell



Exponential concentration of observable readouts

$\langle O \rangle_x$ concentrates exponentially in the **system size** towards an **input-independent value**.

Exponential concentration of observable readouts

$\langle O \rangle_x$ concentrates exponentially in the **system size** towards an **input-independent value**.

Deterministic concentration

$$|\langle O \rangle_x - \mu| \leq \beta \sim \exp(-n)$$

Probabilistic concentration

$$\Pr [|\langle O \rangle_x - \mu| \geq \delta] \leq \frac{\beta}{\delta^2} \sim \exp(-n)$$

Exponential concentration of observable readouts

$\langle O \rangle_x$ concentrates exponentially in the **system size** towards an **input-independent value**.

Deterministic concentration

$$|\langle O \rangle_x - \mu| \leq \beta \sim \exp(-n)$$

Probabilistic concentration

$$\Pr [|\langle O \rangle_x - \mu| \geq \delta] \leq \frac{\beta}{\delta^2} \sim \exp(-n)$$

Consequences

$$\text{Sampling error} \sim 1/\sqrt{N_{\text{shot}}} \longrightarrow N_{\text{shot}} \sim \exp(n)$$

in order to estimate $\langle O \rangle_x$ accurately
to distinguish the two inputs x, x'

Exponential concentration of observable readouts

$\langle O \rangle_x$ concentrates exponentially in the **system size** towards an **input-independent value**.

Deterministic concentration

$$|\langle O \rangle_x - \mu| \leq \beta \sim \exp(-n)$$

Probabilistic concentration

$$\Pr [|\langle O \rangle_x - \mu| \geq \delta] \leq \frac{\beta}{\delta^2} \sim \exp(-n)$$

Consequences

$$\text{Sampling error} \sim 1/\sqrt{N_{\text{shot}}} \longrightarrow N_{\text{shot}} \sim \exp(n)$$

in order to estimate $\langle O \rangle_x$ accurately
to distinguish the two inputs x, x'

→ **Barren Plateaus** in VQAs


→ **Generalization error** in non-VQAs learning model:

Quantum Kernels Thanasilp, S., Wang, S., Cerezo, M. *et al. Nat Commun* **15**, 5200 (2024)

+ **QELMs** + **QRC** W. Xiong, ... TC, Z. Holmes, *Quantum Machine Intelligence* (2025)


W. Xiong, ... TC, S. Thanasilp, *under review in npj QI*

Sources of concentration in QELM




of *both* encoding and reservoir
(2-design ~ extreme scrambling)


Probabilistic Concentration



Probabilistic Concentration



Deterministic Concentration



Deterministic Concentration

In QELM, somewhat similar story to VQAs

A tug of war between **high expressivity** and **avoiding exponential concentration**



Results for Quantum Reservoir Computing (QRC)

Role of scrambling and noise in temporal information processing with quantum systems

Weijie Xiong,^{1,2} Zoë Holmes,^{1,2} Armando Angrisani,^{1,2}
Yudai Suzuki,^{1,2} Thiparat Chotibut,³ and Supanut Thanasilp^{1,2,3}

¹*Institute of Physics, Ecole Polytechnique Fédérale de Lausanne (EPFL), Lausanne, Switzerland*

²*Centre for Quantum Science and Engineering, Ecole Polytechnique Fédérale de Lausanne (EPFL), Lausanne, Switzerland*

³*Chula Intelligent and Complex Systems Lab, Department of Physics,
Faculty of Science, Chulalongkorn University, Bangkok, Thailand*

(Dated: May 16, 2025)

Static Input



Extend to multi-step evolution

Time-series Inputs

$$\{\rho_{a_0}\}$$





$$\{\rho_{a_1}, \rho_{a_2}, \dots, \rho_{a_t}\}$$



Concentration still happens, but not too bad at early times

Theorem 1 (informal) *The output variance of some observable O at some large time t under extreme scrambling reservoir dynamics vanishes exponentially with the system size: $\text{Var}_{U \sim \mathbb{U}(d_a d_h)}[\langle O \rangle_t] \in \mathcal{O}\left(\frac{\text{Tr}[O^2]}{d_a^2 d_h^3}\right)$, where $d_a = 2^{n_a}$ and $d_h = 2^{n_h}$.*

- For large t , output concentrates in the system size; but *no* further concentration in time.
- Scalability barrier** for large QRP: output concentrates towards an input-independent mean!
- Consequence: **poor generalization**, despite guaranteed trainability (linear regression).




Proof strategy: express temporal correlation as a (larger) spatial correlation

Step 1

(embed time series into space)

Step 2

(recast into a standard Haar integration form)




Proof strategy: express temporal correlation as a (larger) spatial correlation

Step 1

(embed time series into space)

Step 2

(recast into a standard Haar integration form)




$$\langle O \rangle_t = \sum_{\mathbf{X}_{h_{t-1}}} \text{Tr} \left[(X_{h_1}, \mathcal{I}_a; X_{h_2}, \mathcal{I}_a; \dots; X_{h_{t-1}}, \mathcal{I}_a; O) U^{\otimes t} (\rho_{h_0}, \rho_{a_1}; X_{h_1}, \rho_{a_2}; X_{h_2}, \rho_{a_3}; \dots; X_{h_{t-1}}, \rho_{a_t}) (U^\dagger)^{\otimes t} \right]$$

- $2t$ -design assumption is stronger than the typical 2-design

Storyline of quantum algorithms on NISQ machines (up to now)

This applies to VQAs, Quantum Neural Networks, Quantum Kernels, QELM, and QRC


1-20 qubits
(promising candidates)



Storyline of quantum algorithms on NISQ machines (up to now)

This applies to VQAs, Quantum Neural Networks, Quantum Kernels, QELM, and QRC

1-20 qubits
(promising candidates)



40+ qubits
(regime with hopes for quantum advantage)



Curse of Dimensionality
(Exponential Concentrations of Outputs)

Can't noise be harnessed as computational resources?



Can't noise be harnessed as computational resources?



Perhaps the secrets lie here!






Random noise promotes slow heterogeneous synaptic dynamics important for robust working memory computation

Nuttida Rungratsameetaweemana^{a,b,1}, Robert Kim^{b,c,1} , Thiparat Chotibut^{d,2} , and Terrence J. Sejnowski^{b,e,f,2} 


Affiliations are included on p. 11.

Edited by Tirin Moore, Stanford University School of Medicine, Stanford, CA; received September 26, 2023; accepted December 6, 2024




Acknowledgement

Mehrad Sahebi Giorgio Facelli Weijie Xiong (EPFL) Supanut Thanasilp



Owen Agnel (Oxford)

Funding Acknowledgement



CHICS



Chulalongkorn U
Thailand
Zoe Holmes



EPFL

Contact

Thiparat Chotibut



Chulalongkorn U
Thailand



@ThiparatC



thiparatc@gmail.com


Why QELM and QRC? A Brief Detour: The Quest for Quantum Advantages

✗ Ideal (Fault-tolerant) quantum computational advantages

Textbook algorithms: Shor's, Grover's, HHL, etc.

✓ Noisy Intermediate-Scale Quantum (NISQ) Era

Variational Quantum Algorithms (VQAs)



A unifying account of warm start guarantees for patches of quantum landscapes

Hela Mhiri,^{1,2,*} Ricard Puig,^{1,*} Sacha Lerch,¹ Manuel S. Rudolph,¹
Thiparat Chotibut,³ Supanut Thanasilp,^{1,3} and Zoë Holmes¹

